

Р

VERTICAL TERMINATION (SCALE: 3'' = 1' - 0''

Publish Date: 08.2017 Δ Δ \triangleleft UNDERLAYMENT SEALED @ SEALANT AND BACKER ROD CAULK JOINT 4 Δ Δ \triangleleft Δ STONEWOOD 3/8' Δ EXTERIOR PANEL OR 5/16", 1/2", CUSTOM THICKNESSES AVAILABLE. Δ Δ 1/2 VAPROSHIELD[®] REVEALSHIELD[™] UV STABLE WATER RESISTIVE 1" VAPOR PERMEABLE AIR BARRIER \triangleleft MEMBRANE FOR OPEN JOINT CLADDING SYSTEMS STONEWOOD EXTERIOR PANEL Δ HIGH PERFORMANCE. PREFINISHED, EXTRUDED ALUMINUM VERTICAL FURRING (PT # EFEB) STAINLESS STEEL NEOPRENE WASHERED FASTENERS SEALANT AND BACKER ROD NOT BY NORTHCLAD®

- Note: Fasten furring into aligned stud or horizontal blocking. Spacing per engineering, 2'-0" O.C. Max
- For further information regarding Stonewood Architectural Panels call: 800-450-0051 or visit: www.Stonewoodpanels.com.
- For details without exterior insulation, or to download the CAD version of this detail, please see www.northclad.com.

Important Note:

Fiberesin Industries and Northclad Rainscreen Solutions independently warrant the performance of their products. Please contact Fiberesin Industries or NorthClad Rainscreen Solutions or visit Stonewoodpanels.com and Northclad.com for more warranty information.



Fiberesin Industries, Inc. | N48W37031E. Wisconsin Ave. | Oconomowoc, WI 53066-3146 | Phone: 262-567-4427 | www.stonewoodpanels.com | © Fiberesin 2017