

Care, Handling, and Storage

MATERIAL RECEIPT

- Verify condition of package.
- All product is quoted FCA factory. If there is visible damage, it is the responsibility of the buyer to file a freight claim for any damage within 24 hours of receipt.

PACKAGING AND MOVING

- Keep panels on pallets
- Fasten panels using straps within vehicle
- Protect edges with packing material such as: corners/blankets

HANDLING AND STORAGE

Do not scratch the surface of the panel during handling, machining and installation

- Panels are shipped with protective paper strips between each panel.
- Paper strips are intended to protect the surface of panels during transportation.
- Keep paper strips in place until ready to install
- Always use the paper strips when stacking panels.
- Keep panels dry and stored indoors in original packaging until installation
- Keep load stored in outer wrap until use. Remove pallet straps once load is moved to storage area
- Store panels on a smooth, dry, flat surface, ensuring there are no bends or bowing in the load
- Store panels flat
- Reseal protective wrap if partial load is used
- Damage resulting from improper storage will void the warrantee



- **Do not store panels on edges or uneven surfaces**
- **Do NOT let panels slip or slide into each other**
- **Do not** store directly on cold concrete floors as moisture may migrate
- **Do not** store under heating units or air conditioning units
- **Damage resulting from improper storage will void the warrantee**